

EPO-Guard[™] EPO-200 Part A

Moisture Vapor Barrier

SAFETY DATA SHEET

SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

Product Name:	EPO-Guard™ EPO-200 Part A	
Revision Date:	Feb 23, 2024	Date Printed: Feb 23, 2024
Version:	1.0	Supersedes Date: N.A.
Manufacturer's Name:	Res-Tek, Inc.	
Address:	110 Riverside Drive SW Cartersville, GA, 30120 United States of America	
Emergency Phone:	CHEMTREC 24 hr. 1-800-424-9300 / 1 (703)	527-3887 (Collect calls accepted).
Information Phone Number:	1-888-737-8351 / 1-770-427-4034	
Product/Recommended Uses:	Industrial Flooring Resin	

SECTION 2) HAZARDS IDENTIFICATION

Classification

Eye Irritation - Category 2A

Skin Irritation - Category 2

Skin Sensitizer - Category 1

Safety data sheet prepared in accordance to the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

Pictograms



Signal Word

Warning

Hazardous Statements - Health

H319 - Causes serious eye irritation

- H315 Causes skin irritation
- H317 May cause an allergic skin reaction

Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.

- P102 Keep out of reach of children.
- P103 Read label before use.

Precautionary Statements - Prevention

- P264 Wash thoroughly after handling.
- P280 Wear protective gloves, protective clothing, eye protection/face protection.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P272 - Contaminated work clothing should not be allowed out of the workplace.

Precautionary Statements - Response

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical advice/attention.

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P321 - Specific treatment (see First-Aid on this label).

P362 + P364 - Take off contaminated clothing. And wash it before reuse.

P333 + P313 - If skin irritation or a rash occurs: Get medical advice/attention.

Precautionary Statements - Storage

No precautionary statement available.

Precautionary Statements - Disposal

P501 - Dispose of contents/container in accordance with local/national/international regulations.

SECTION 3) COMPOSITION/INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
0025068-38-6	BISPHENOL A DIGLYCIDYL ETHER POLYMER	60% - 70%
0068609-97-2	EPOXIDE RESINS, LIQUID	10% - 20%
0028064-14-4	PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETH	10% - 20%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

SECTION 4) FIRST-AID MEASURES

Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

Eye Contact

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention. Avoid direct contact. Wear chemical protective gloves, if necessary.

Skin Contact

Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes. If skin irritation or a rash occurs: Get medical advice/attention. Wash contaminated clothing before re-use or discard.

Ingestion

Rinse mouth. If you feel unwell/If concerned: Call a POISON CENTER/doctor.

Most important symptoms and effects, both acute and delayed

No data available.

Indication of any immediate medical attention and special treatment needed

Treat according to symptoms (decontamination, vital functions), no known specific antidote. Treatment should be supportive and based on the judgement of the physician in response to the reaction of the patient.

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Small Fire : Dry chemical, foam, carbon dioxide, water-spray or alcohol-resistant foam. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Large Fire : Water spray, fog or alcohol-resistant foam.

Unsuitable Extinguishing Media

Do not use straight stream of water.

Specific Hazards in Case of Fire

Fire will produce irritating gases.

Fire-fighting Procedures

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Cool containers with flooding quantities of water until well after fire is out. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Special Protective Actions

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Emergency Procedure

Isolate hazard area and keep unauthorized personnel away. Stay uphill and/or upstream. Ventilate closed spaces before entering. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Recommended Equipment

Wear chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA).

Personal Precautions

Avoid breathing vapor or mist. Do not get on skin, eyes or clothing.

Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

Methods and Materials for Containment and Cleaning up

Absorb Liquids in vermiculite, dry sand, earth, or similar inert material and deposit in sealed containers for disposal. Ventilate area after clean-up is complete.

SECTION 7) HANDLING AND STORAGE

General

Wash hands after use. Avoid breathing vapor or mist. Use good personal hygiene practices. Eating, drinking and smoking in work areas is prohibited. Remove contaminated clothing and protective equipment before entering eating areas. Eyewash stations and showers should be available in areas where this material is used and stored All containers must be properly labelled. Do not get in eyes, on skin, or on clothing.

Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source. Report ventilation failures immediately.

Storage Room Requirements

Store in a cool, dry, well ventilated area, away from sources of ignition and incompatibilities. Keep containers securely sealed when not in use. Containers that have been opened must be carefully resealed to prevent leakage. Indoor storage should meet OSHA standards and appropriate fire codes. Empty containers retain residue and may be dangerous.

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye protection

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids.

Skin Protection

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 should be followed. Check with respiratory protective equipment suppliers.

Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

None of the chemicals in Section 3 are regulated under "ACGIH_carcinogen", "ACGIH_Notations", "ACGIH_TLV_Basis", "ACGIHsmg", "ACGIHsppm", "ACGIHtmg", "ACGIHtppm", "CAN_AL_Carcinogen", "CAN_AL_Notation", "CAN_ALsmg", "CAN_ALsppm", "CAN_ALtmg", "CAN_ALtppm", "CAN_ONsmg", "CAN_ONsppm", "CAN_ONtmg", "CAN_ONtppm", "CAN_QCVECDmg - CANADA_QUEBEC VALEUR D" "EXPOSITION DE COURTE DURÉE_mg", "CAN_QCVECDppm - CANADA_QUEBEC VALEUR D" EXPOSITION DE COURTE DURÉE_mg", "CAN_QCVECDppm - CANADA_QUEBEC VALEUR D" EXPOSITION DE COURTE DURÉE_mg", "CAN_QCVECDppm - CANADA_QUEBEC VALEUR D" EXPOSITION MOYENNE PONDÉRÉE_ppm", "CAN_QCVEMPmg - CANADA_QUEBEC VALEUR D" EXPOSITION MOYENNE PONDÉRÉE_ppm", "CANsppm", "CAN_QCVEMPppm - CANADA_QUEBEC VALEUR D" EXPOSITION MOYENNE PONDÉRÉE_ppm", "CANsppm", "CANsppm", "CANtmg", "CANtppm", "NIOSH_carcinogen", "nioshsmg", "nioshtmg", "nioshtmg", "OSHA_SkinDesignation", "OSHA_Tables_Z1_Z2_Z3", "OSHACarcinogen - OSHA Carcinogen", "OSHAsmg", "OSHAtmg", "OSHAtppm"

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance

Liquid

Color.	Amber.
Odor	Low.
Odor Threshold (ppm)	Not available.
pH (Value)	Not available.
Melting Point (°C) / Freezing Point (°C)	Not available.
Boiling point/boiling range (°C):	Not available.
Flash Point (°C)	Not available.
Evaporation Rate	Not available.
Flammability (solid, gas)	Not available.
Explosive Limit Ranges	Not available.
Vapour pressure (mmHg)	Not available.
Vapour Density (Air=1)	Not available.
Density (g/ml)	1.159 @ 25 °C (9.67 lb/gal).
Specific Gravity	1.159.
Solubility (Water)	Not available.
Solubility (Other)	Not available.
Partition Coefficient (n-Octanol/water)	Not available.
Auto Ignition Point (°C)	Not available.
Decomposition Temperature (°C)	Not available.
Dynamic Viscosity (cPs @ 25°C)	800.
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Other information	VOC Content: 0 g/l.

SECTION 10) STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical Stability

Stable under normal storage and handling conditions.

Possibility of Hazardous Reactions/Polymerization

Will not occur.

Conditions To Avoid

Avoid heat, sparks, flame and contact with incompatible materials

Incompatible Materials

Strong bases, acids, and oxidizing agents.

Hazardous Decomposition Products

Oxides of carbon.

SECTION 11) TOXICOLOGICAL INFORMATION

Acute Toxicity

Based on available data, the classification criteria are not met.

The Acute Toxicity Estimate (ATE) for an oral exposure to this mixture is >5000 mg/kg body weight

The Acute Toxicity Estimate (ATE) for a dermal exposure to this mixture is >5000 mg/kg body weight

The Acute Toxicity Estimate (ATE) for an inhalation (vapour) exposure to this mixture is >20 mg/l

The Acute Toxicity Estimate (ATE) for an inhalation (dust and mist) exposure to this mixture is >5 mg/l $\,$

Aspiration Hazard

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity

Based on available data, the classification criteria are not met.

Reproductive Toxicity

Based on available data, the classification criteria are not met.

Respiratory/Skin Sensitization

May cause an allergic skin reaction

Serious Eye Damage/Irritation

Causes serious eye irritation

Skin Corrosion/Irritation

Causes skin irritation

Specific Target Organ Toxicity - Repeated Exposure

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

Based on available data, the classification criteria are not met.

Likely Routes of Exposure

Inhalation, Ingestion, Skin contact, Eye contact

Potential Health Effects - Miscellaneous

0025068-38-6 BISPHENOL A DIGLYCIDYL ETHER POLYMER

The following medical conditions may be aggravated by exposure: skin disorders. Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guin 0068609-97-2 Epoxide resins, liquid.

The following medical conditions may be aggravated by exposure: allergies, eczema, skin disorders. Irritating to the mouth, throat and stomach. Potential skin sensitizer that may cause allergic reactions and contact dermatitis resulting in severe irritation, dryness, and cracking of the skin.

SECTION 12) ECOLOGICAL INFORMATION

Toxicity

Based on available data, the classification criteria are not met.

Persistence and Degradability

No data available.

Bioaccumulative Potential

No data available.

Mobility in Soil

No data available.

Other Adverse Effects

No data available.

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal

It is the responsibility of the user of the product to determine at the time of disposal whether the product meets local criteria for hazardous waste. Waste management should be in full compliance with national, state and local laws. Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes.

SECTION 14) TRANSPORT INFORMATION			
Display Order	U.S. DOT Information	IMDG Information	IATA Information
UN Number	Not Regulated	Not Regulated	Not Regulated

UN proper shipping name	N/A	N/A	N/A
Transport Hazard class(es)	Not Applicable	Not Applicable	Not Applicable
Packing group	Not Applicable	Not Applicable	Not Applicable
Hazardous substance (RQ)	Not Applicable	Not Applicable	Not Applicable
Environmental hazards	No Data Available	No Data Available	No Data Available
Special precautions for user	No Data Available	No Data Available	No Data Available
Transport in bulk according to Annex II of MARPOL and the IBC code	No Data Available	No Data Available	No Data Available

SECTION 15) REGULATORY INFORMATION

CAS	Chemical Name	% By Weight	Regulation List
0025068-38-6	BISPHENOL A DIGLYCIDYL ETHER POLYMER	60% - 70%	DSL, SARA312, TSCA, TSCA_CDR - TSCA - Chemical Data Reporting (CDR) Rule, TSCATS - TOXIC SUBSTANCES CONTROL ACT TEST SUBMISSIONS
0068609-97-2	EPOXIDE RESINS, LIQUID	10% - 20%	DSL, SARA312, TSCA, TSCA_UVCB - CHEMICAL SUBSTANCES OF UNKNOWN OR VARIABLE COMPOSITION, COMPLEX REACTION PRODUCTS AND BIOLOGICAL MATERIALS, TSCA_CDR - TSCA - Chemical Data Reporting (CDR) Rule, TSCATS - TOXIC SUBSTANCES CONTROL ACT TEST SUBMISSIONS
0028064-14-4	PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETH	10% - 20%	DSL, SARA312, TSCA, TSCA_UVCB - CHEMICAL SUBSTANCES OF UNKNOWN OR VARIABLE COMPOSITION, COMPLEX REACTION PRODUCTS AND BIOLOGICAL MATERIALS, TSCA_CDR - TSCA - Chemical Data Reporting (CDR) Rule, TSCATS - TOXIC SUBSTANCES CONTROL ACT TEST SUBMISSIONS

Product does not contain any chemicals listed under California Proposition 65

SECTION 16) OTHER INFORMATION

Glossary

ACGIH - American Conference of Governmental Industrial Hygienists; CAS - Chemical Abstracts Service ; Chemtrec - Chemical Transportation Emergency Center; DSL - Domestic Substances List; ESL- Effects screening levels; GHS - "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations; HMIS - Hazardous Material Information Service; IATA - Dangerous Goods Regulations (DGR) for the air transport (IATA); IMDG - International Maritime Dangerous Goods Code; LC - Lethal Concentration; LD - Lethal Dose; NFPA - National Fire Protection Association; OEL - Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL - Permissible Exposure Limit; SARA 313 - Superfund Amendments and Reauthorization Act, Section 313; SCBA - Self Contained Breathing Apparatus; ppm - parts per million; STEL - Short-term exposure limit; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act Public Law 94-469; TWA - Time-weighted average; US DOT- US Department of Transportation.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.